

3D Milling Machine

MDX-40R

*Quickly and Inexpensively Create Prototypes,
Parts and Mock-Ups*
MDX-40 – The Perfect In-House SRP® Solution



MODELA Player4 &
on-screen, operation panel
to customize settings

Features:

- Includes Rotary Axis Unit for unattended two- and four-sided milling
- Work area is perfect for midsize jobs -- 305mm(X) x 305mm(Y) x 105mm(Z) (12" x 12" x 4.12")
- Provides high speed performance with 15,000 rpm spindle
- Includes easy-to-use Roland software -- MODELA Player 4, CAM software, Virtual MODELA simulation software, etc.
- Combines precision 3D scanning and milling capabilities into one compact device
- Emergency stop switch and machine cover ensure safety and promote clean, quiet work environment

Specifications

		MDX-40
Acceptable materials		Resins such as chemical wood and modeling wax (metal not supported)
X, Y, and Z operation strokes		305 (X) x 305 (Y) x 105 (Z) mm (12 (X) x 12 (Y) x 4-1/8 (Z) in.)
Distance from spindle tip to table		Maximum 125 mm (4-15/16 in.)
Table size		305 (W) x 305 (D) mm (12 (W) x 12 (D) in.)
Loadable workpiece weight		4 Kg (8.8 lb)
XYZ-axis motor		Stepping motor
Feed rate		XY-axis : 0.1 to 50 mm/sec. (0.0039 to 1.9 in./s) Z-axis : 0.1 to 30 mm/sec. (0.0039 to 1.1 in./s)
Software resolution		0.01 mm/step (0.00039 in./step)
Mechanical resolution		0.002 mm/step (0.0001 mm/step)
Spindle motor		DC brushless motor, Maximum 100W
Spindle type		Modeling spindle
Spindle rotation		4500 to 15000 rpm
Tool chuck		Collet
Interface		USB connector, sensor connector, expansion connector
Power supply	Voltage and frequency	AC100 to 240 ± 10%, 50/60 Hz
	Required power capacity	2.1 A
Power consumption		Approx. 210W
Acoustic noise level		No-load operation : 56 dB (A) or less, standby : 42 dB (A) or less (According to ISO7779)
Dimensions		669 (W) x 760 (D) x 554 (H) mm (26-3/8 (W) x 29-15/16 (D) x 21-13/16 (H) in.)
Weight		66 Kg (146 lb)
Packed dimensions		785 (W) x 885 (D) x 735 (H) mm (31 (W) x 35 (D) x 29 (H) in.)
Packed weight		73 Kg (161 lb)
Operation temperature		5 to 40°C (41 to 104°F)
Operation humidity		35 to 80 % (no condensation)
Accessories		Power cord, collet, sensor, hexagonal wrench, hexagonal screw drivers, spanners, Roland Software Package CD-ROM, MODELA Player4 CD-ROM, user's manual, Roland Software Package installation and setup guide, MODELA Player4 installation and setup guide

Options

dia. = shank diameter, L = overall length, W = blade width

unit: mm dia. = flute diameter, R = flute radius, l = flute length,
d = shank diameter, L = overall length, NT = number of flutes

Item	Model	Description
Engraving cutters (for plastic)	ZEC-A4013	Cemented carbide dia.4.36 x 165(L) x 0.127(W)
	ZEC-A4025	Cemented carbide dia.4.36 x 165(L) x 0.254(W)
	ZEC-A4051	Cemented carbide dia.4.36 x 165(L) x 0.508(W)
	ZEC-A4076	Cemented carbide dia.4.36 x 165(L) x 0.762(W)
Engraving cutters, quarter round (for plastic)	ZEC-A4013-QR	Cemented carbide dia.4.36 x 165(L) x 0.13(W)
	ZEC-A4025-QR	Cemented carbide dia.4.36 x 165(L) x 0.25(W)
Engraving cutters, parallel (for plastic)	ZEC-A4150	Cemented carbide dia.4.36 x 165(L) x 1.52(W)
	ZEC-A4190	Cemented carbide dia.4.36 x 165(L) x 1.91(W)
	ZEC-A4230	Cemented carbide dia.4.36 x 165(L) x 2.29(W)
	ZEC-A4320	Cemented carbide dia.4.36 x 165(L) x 3.175(W)
	ZEC-A4380	Cemented carbide dia.4.36 x 165(L) x 3.81(W)
	ZEC-A4430	Cemented carbide dia.4.36 x 165(L) x 4.34(W)

Item	Model	Description
Collets (for end-mills)	ZC-23	dia.6mm, dia.5mm, dia.4mm, dia.3mm, including 1pc. each
	ZC-23-3175	dia.3.175mm
	ZC-23-6	dia.6 mm
	ZC-23-6.35	dia.6.35mm
Collets (for diamond cutter)	ZC-E436	dia.4.36mm
Adhesive sheet for securing material	AS-10	210mm x 140mm, including 10 sheets
Chemical wood	ZSM-SS	97mm x 147mm x 50mm, including 5 pcs.
Wax	ZW-200	75mm x 175mm x 38mm, including 10 pcs.

Item	Model	Description
Square end-mills	ZHS-100	High speed steel dia.1 3(l) x 6(d) x 50(L) x 2NT
	ZHS-200	High speed steel dia.2 6(l) x 6(d) x 50(L) x 2NT
	ZHS-300	High speed steel dia.3 10(l) x 6(d) x 50(L) x 2NT
	ZHS-400	High speed steel dia.4 8(l) x 6(d) x 60(L) x 2NT
	ZHS-500	High speed steel dia.5 10(l) x 6(d) x 60(L) x 2NT
	ZHS-600	High speed steel dia.6 15(l) x 6(d) x 55(L) x 2NT
	ZHS-3015	High speed steel dia.3 15(l) x 6(d) x 50(L) x 2NT including 2pcs.
	ZUS-300	Cemented carbide dia.3 15(l) x 3(d) x 60(L) x 2NT
	ZUS-400	Cemented carbide dia.4 20(l) x 4(d) x 60(L) x 2NT
	ZUS-500	Cemented carbide dia.5 25(l) x 5(d) x 60(L) x 2NT
Ball end-mills	ZUB-150	Cemented carbide R1.5 10(l) x 3(d) x 65(L) x 2NT
	ZUB-200	Cemented carbide R2.0 12(l) x 4(d) x 65(L) x 2NT
	ZUB-250	Cemented carbide R2.5 20(l) x 5(d) x 65(L) x 2NT
	ZUB-300	Cemented carbide R3.0 30(l) x 6(d) x 65(L) x 2NT

Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. Three-dimensional shapes may be protected under copyright. Customers are responsible for observing laws and ordinances when scanning. All trademarks are the property of their respective owners.



AUTHORIZED DEALER:

PO Box 649 Milsons Point
NSW 1565 Australia
t : 02 8212 4822
f : 02 8905 9237
e : email@qubic.com.au



www.rolanddg.com

Qubic